



## **DECORATIVE WATER-BASED INTERIOR PRODUCT GROUP**

# **Tempo Super Ceiling**

### **PRODUCT DESCRIPTION**

Acrylic-based, matte, decorative interior white ceiling paint with high-coverage.

### **FEATURES**

Water-based with a high level of breathability. Matte and smooth finish. Adheres perfectly to surfaces. Provides high-coverage. Does not lead to blistering or flaking when applied correctly.

### **APPLICATION SURFACES**

Intended for interior ceilings, such as mineral-based, previously painted, puttied, satin plastered and/or plasterboard surfaces with no dusting behavior.

### **APPLICATION**

Application surfaces should be smooth, dry, clean, solid, and able to bear the paint. Remove any stain, dust, mold grease and loose layers. Perform required surface corrections before application. Comply with defined setting periods on concrete, exposed concrete and new plastered surfaces (28 days). Ensure that ambient and surface temperatures are between +5 °C and 30 °C during application. Apply using a brush, roller or spray gun. Our products should be applied on substructure surfaces that are built in line with 30.06.2007 dated General Construction Specifications No. 26568.

### **Airless Spraying:**

Pressure: 140 bar Nozzle Angle: 50°

Nozzle Size (inch): 0.019"

Thinning (Water): 10-15% (Volume)

### **THINNING RATIO**

Recommended to be applied in two coats after diluting by 20-25% with clean water. For spray gun applications, applied in a single coat after diluting by 10-15% with clean water.



### **DRYING TIME (at 20 °C, 65% RH)**

First drying: 30-60 minutes

Application of second coat: 3-4 hours

Final drying: 24 hours (drying time may increase at higher relative humidity and lower temperatures).

### **CONSUMPTION**

6-10 m<sup>2</sup> in a single coat with 1 kg. Perform a controlled sample run to estimate the precise consumption.

### **STORAGE**

May be stored for 3 years in its unopened packaging in a cool and dry environment protected against frost and direct sunlight.

### **PACKAGING**

17.5 kg, 10 kg, 3.5 kg

### **WARNING WORD**

Caution

### **HAZARD PHRASE**

H317 May cause an allergic skin reaction.

### **PRECAUTIONARY PHRASES**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P321 Specific treatment required (see label).

P363 Wash contaminated clothing before reuse.

P333+P313 If skin irritation or a rash occurs: Get medical advice/attention.

P501 Dispose of contents/container in accordance with local, regional, national and international regulations.



Complies with TS 5808/2012.



Complies with the G communiqué.

TSE

Gloss: Matte

Granule Size: Fine

Coverage Strength: Class 2 (7 m<sup>2</sup>/L)

Wet Scrub Resistance: Class 5

This technical sheet is prepared based on laboratory data at normal conditions, consult technical personnel for details that are not provided above. Otherwise, the manufacturing company cannot be held responsible for failures that may arise due to lack of knowledge. Our company reserves the right to change this information.

**This product is manufactured by Betek A.Ş. with certificate of conformity to the standards TS EN ISO 9001, TS EN ISO 14001, TS 18001, TS EN ISO 50001, TS ISO 10002, TS ISO/IEC 27001.**

Rev2 July 2019

BETEK BOYA VE KİMYA SAN. A.Ş.

Gebze Organize Sanayi Bölgesi Tembelova Alanı 3200. Sokak No: 3206 Gebze / KOCAELİ - TURKEY

Phone: +90 (0216) 571 11 90 (pbx)

[www.tempoboya.com.tr](http://www.tempoboya.com.tr)