



DECORATIVE WATER-BASED INTERIOR PRODUCT GROUP

Tempo Universal Primer

PRODUCT DESCRIPTION

Acrylic copolymer-based, white-pigmented primer. High coverage and adherence.

FEATURES

Improves adherence by playing a binding bridge role between the paint and the surface. Reduces paint consumption and saves time by preventing over absorption of the top coat paint by the surface.

APPLICATION SURFACES

Applied as a primer on interior or exterior raw plastered surfaces, concrete, exposed concrete, MDF, precast concrete panel, OSB, brick, paste and surfaces which will be painted for the first time and faded previously painted surfaces or which are desired to be changed for decorative purposes.

APPLICATION

Application surfaces should be smooth, dry, clean, solid, and able to bear the paint. Remove any dirt, dust, mold grease and loose layers from the application surface, perform required surface corrections and prime with Tempo Universal Primer. Comply with defined setting periods on concrete, exposed concrete and new plastered surfaces (28 days). Ensure that ambient and surface temperatures are between +5 °C and 30 °C during application. Apply using a brush, roller or spray gun. Our products should be applied on substructure surfaces that are built in line with 30.06.2007 dated General Construction Specifications No. 26568.

Airless Spraying:

Pressure: 120-140 bar

Nozzle Angle: 50°

Nozzle Size (inch): 0.013"

Thinning (Water): 5% (Volume)

THINNING RATIO

Thin by 10-15% maximum with water in brush and roller applications. Thin by 5% maximum with clean water in spraying.

BETEK BOYA VE KİMYA SAN. A.Ş.

Gebze Organize Sanayi Bölgesi Tembelova Alanı 3200. Sokak No: 3206 Gebze / KOCAELİ - TURKEY

Phone: +90 (0216) 571 11 90 (pbx)

www.tempoboya.com.tr

**DRYING TIME (at 20 °C, 65% RH):**

First drying: 1-2 hours

Paint application: 5-6 hours

CONSUMPTION

4.5 - 7.5 m² can be primed in a single coat with 1 kg. Perform a controlled sample run to estimate the precise consumption.

STORAGE

May be stored for 3 years in its unopened packaging in a cool and dry environment protected against frost and direct sunlight.

PACKAGING

20 kg, 3.5 kg

WARNING WORD

Caution

HAZARD PHRASE

H317 May cause an allergic skin reaction.

PRECAUTIONARY PHRASES

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P321 Specific treatment required (see label).

P363 Wash contaminated clothing before reuse.

P333+P313 If skin irritation or a rash occurs: Get medical advice/attention.

P501 Dispose of contents/container in accordance with local, regional, national and international regulations.

BETEK BOYA VE KİMYA SAN. A.Ş.

Gebze Organize Sanayi Bölgesi Tembelova Alanı 3200. Sokak No: 3206 Gebze / KOCAELİ - TURKEY

Phone: +90 (0216) 571 11 90 (pbx)

www.tempoboya.com.tr



Pose No.

15.540.1205, 15.540.1206, 15.540.1207, 15.540.1211, 15.540.1214, 15.540.1215, 15.540.1217, 15.540.1218, 15.540.1220, 15.540.1221, 15.540.1232, 15.540.1233, 15.540.1301, 15.540.1302, 15.540.1303

Rate No.

10.300.1151

This technical sheet is prepared based on laboratory data at normal conditions, consult technical personnel for details that are not provided above. Otherwise, the manufacturing company cannot be held responsible for failures that may arise due to lack of knowledge. Our company reserves the right to change this information.

This product is manufactured by Betek A.Ş. with certificate of conformity to the standards TS EN ISO 9001, TS EN ISO 14001, TS 18001, TS EN ISO 50001, TS ISO 10002, TS ISO/IEC 27001.

Rev1 May 2019

BETEK BOYA VE KİMYA SAN. A.Ş.

Gebze Organize Sanayi Bölgesi Tembelova Alanı 3200. Sokak No: 3206 Gebze / KOCAELİ - TURKEY

Phone: +90 (0216) 571 11 90 (pbx)

www.tempoboya.com.tr